

HOW DO THE CONNECTORS AND COUPLINGS WORK?









^{*} IP54 and IP65 connections should be sealed with silicon sealer and covered with heat shrink.

COUPLINGS

CATALOG NO.	TO BE USED WITH	LENGTH
LEDR-8M-A	SMD3528 Tape light (Part numbers with "D3")	0.62" x 0.55 (W)
LEDR-10M-A	SMD5050 Tape light (Part numbers with "D5")	0.62" x 0.55 (W)
LEDR-10M-A-RGB	RGB SMD5050 Tape light (Part numbers with "D5 RGB")	

CONNECTORS

CATALOG NO.	TO BE USED WITH	LENGTH
LEDR-8M-B	SMD3528 Tape light (Part numbers with "D3")	8"
LEDR-10M-B	SMD5050 Tape light (Part numbers with "D5")	8"
LEDR-10M-B-RGB	RGB SMD5050 Tape light (Part numbers with "D5 RGB")	7-1/2"

COUPLINGS WITH WIRE

CATALOG NO.	TO BE USED WITH	LENGTH
LEDR-8M-C	SMD3528 Tape light (Part numbers with "D3")	8"
LEDR-10M-C	SMD5050 Tape light (Part numbers with "D5")	8"
LEDR-10M-C-RGB	RGB SMD5050 Tape light (Part numbers with "D5 RGB")	8"

WESTGATE MFG

SAME DAY