178

LED EXIT & EMERGENCY LIGHTING I COMBINATION LED



TECHNICAL SPECIFICATIONS:

- :: High-impact thermo-plastic LED exit and emergency light
- :: Even illumination across the face without LED imaging
- :: Energy-efficient LED panel, 3.2 watts (Red) 3.8 watts (Green), 25-year rated
- :: Two fully adjustable 1-watt glare-fee LED heads for safe egress
- :: 120/277 volt operation (20-40°C)
- :: Top canopy included for ceiling installation
- :: EZ snap-out left or right arrow knock outs
- :: 96V maintenance-free sealed Ni-Cad rechargeable battery for long life
- :: Low profile compact design, available in white or black housing
- :: 90-minute rated with push style test switch and red indicator light
- :: Universal exit: single or double face wall (back) or ceiling mount
- :: Mounting accessories included
- :: UL-listed for damp locations, meets UL924, NFPA 101 Life Safety Code

COMBINATION LED EXIT SIGN & LED EMERGENCY

CATALOG NO.	LETTERS	NUMBER OF FACEPLATES	FACEPLATE	VOLTAGE	BATTERY	CUSTOMIZE
XT-CL-RW-EM	Red on Aluminum	Universal Single/Double	White	120/277	4.8V Ni-Cad	Black Housing
XT-CL-GW-EM	Green on Aluminum	Universal Single/Double	White	120/277	4.8V Ni-Cad	





TECHNICAL SPECIFICATIONS:

- :: High-impact die-cast aluminum LED exit and emergency light
- :: Even illumination across the face without LED imaging
- :: Energy-efficient LED panel, 3.2 watts (Red) 3.8 watts (Green), 25-year rated
- :: Two fully adjustable 3-watt LED, glare-fee heads for safe egress
- :: 120/277 volt operation (20-40°C)
- :: Top canopy included for ceiling installation
- :: EZ snap-out left or right arrow knock outs
- :: 8.4V maintenance-free sealed Ni-Cad rechargeable battery for long life
- :: Low profile compact design, available in white or black housing
- :: 90-minute rated with push style test switch and red indicator light
- :: Universal exit: single or double face wall (back) or ceiling mount
- :: Mounting accessories included
- :: UL-listed for damp locations, meets UL924, NFPA 101

ALUMINUM LED EXIT SIGN WITH ADJUSTABLE LED HEADS

CATALOG NO.	LETTERS	NUMBER OF FACEPLATE	HOUSING	VOLTAGE	BATTERY	CUSTOMIZE
XT-C-ADJ-3RBAEM	Red on Aluminum	Universal Single/Double	Black	120/277	Ni-Cad	Aluminum or white housing
XT-C-ADJ-3GBAEM	Green on Aluminum	Universal Single/Double	Black	120/277	Ni-Cad	

WESTGATE MEG

W W W . W E S T G A T E M F G . C O M T O L L F R E E : 8 7 7 . 8 0 5 . 2 2 5 2 F A X : 8 7 7 . 8 0 9 . 2 2 5







