LSS SERIES Commercial Lighting

Selection:





Customer Name:

Туре:	
'	
88 3/4"	

LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.

Ideal choice for residential, commercial, and industrial lighting. Steady performance and long lifetime. Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below

Features

- High Lumen Efficiency
- Ceiling Mount or Suspended Mount

Technical Specifications

Electrical:

- Voltage: 120-277VAC 60Hz
- Wattage: 55W/ 65W/ 75W/ 90W
- Power Factor: >0.99
- Efficacy: 135 LPW

Mechanical:

- **Black Finish**
- High Lumen Efficiency Lumen
- Lens: Polycarbonate Frosted Lens, Shatter Resistant
- Ceiling Mount or Suspended Mount
- Operating Temperature: -4°F to 122°F
- Housing: Cold-rolled Steel
- IP20, Indoor Use Only
- 5-Year Warranty

Lighting:

- Dimmable: 0~10V Dimming
- Total Lumens: 11745LM Max.
- Color Temperatures: 3000K/ 3500K/ 4000K/ 5000K
- Multi CCT and Power (Switches are inside fixture)
- Reduces Energy Consumption Up to 80% Compared to a Fluorescent Fixture
- Rated life: 50.000 Hrs

Applications:

- LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.
- Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below
- Ideal for residential, commercial, and industrial lighting. Steady performance and long lifetime

Other Models:

90W | 11745LM | LSS-8FT-90W-MCTP








- Color Rendering Index: $CRI \ge 80$

88 3/4"(L) x 2 1/2"(W) x 2 3/5"(H)

- Linkable (Optional Alignment Bracket Available)
- Multi CCT and Power (Switches are inside fixture)



1

Other Views:

Sample Orde Model Size Wa LSS = 8FT = 90 Accessories: Ss-CB2 = ALIGNMENT BRACKET SS-CB2 = ALIGNMENT BRACKET SUSPENSIG CL-TBC-WN = T-BAR CLIP WITH SUSPENSIG CL-CSY = ADJUSTABLE 1/16" 6FT. SUSPEN SUSPENSIG	Wattage 55W 65W 75W 90W ering attage Colo	ICTP-BK Voltage 120~277V or Temp. Housin CTP – ВК	7 8 1(1 ⁻	Lumens 7425LM 3775LM 0125LM 1745LM ACCESS ACCESS SCL-GSY110	Color Temp 3000K 3500K 4000K 5000K ORIES:	B3-U	4-G3	LPW 135
LSS-8FT-90W-MCTP-BK Sample Orde Model Size Wa LSS = 8FT = 90 ACCESSORIES: ank = No Option For Accessories SS-CB2 = ALIGNMENT BRACKET CL-TBC-WN = T-BAR CLIP WITH SUSPENSIN CL-CSY = ADJUSTABLE 1/16" 6FT. SUSPEN	55W 65W 75W 90W ering attage Colo	120~277V or Temp. Housin	7 8 1(1 ⁻	7425LM 3775LM 0125LM 1745LM ACCESS	3000K 3500K 4000K 5000K ORIES:	вз-и	4-G3	135
	65W 75W 90W ering attage Colo	or Temp. Housin	8 1(1 ⁻	ACCESS	3500K 4000K 5000K ORIES:		ALIGNMENT	T (COUPLING
Model Size Wa LSS = 8FT = 90 Accessories: Mark = No Option For Accessories Ss-CB2 = ALIGNMENT BRACKET CL-TBC-WN = T-BAR CLIP WITH SUSPENSIG CL-CSY = ADJUSTABLE 1/16" 6FT. SUSPEN	nttage Cold		<u>g</u>					
Model Size Wa LSS = 8FT = 90 ACCESSORIES: ank = No Option For Accessories SS-CB2 = ALIGNMENT BRACKET CL-TBC-WN = T-BAR CLIP WITH SUSPENSIO CL-CSY = ADJUSTABLE 1/16" 6FT. SUSPEN	nttage Cold		<u>9</u>	SCL-GSY110	SCL-GSY120			
ACCESSORIES: ank = No Option For Accessories IS-CB2 = ALIGNMENT BRACKET CL-TBC-WN = T-BAR CLIP WITH SUSPENSION CL-CSY = ADJUSTABLE 1/16" 6FT. SUSPEN		CTP = BK		SCL-GSY110	SCL-GSY120			
lank = No Option For Accessories SS-CB2 = ALIGNMENT BRACKET CL-TBC-WN = T-BAR CLIP WITH SUSPENSI CL-CSY = ADJUSTABLE 1/16" 6FT. SUSPEN				SCL-GSY110	SCL-GSY120			
SS-CB2 = ALIGNMENT BRACKET CL-TBC-WN = T-BAR CLIP WITH SUSPENSI CL-CSY = ADJUSTABLE 1/16" 6FT. SUSPEN				SCL-GSY110	SCL-GSY120	SCL-TBC-WN	BRA	CKET
CL-GSY10 = HEAVY-DUTY ADJUSTABLE 1/1 DOP GRIPPER & HOOKS - 70 LBS. MAX LOJ CL-GSY20 = HEAVY-DUTY ADJUSTABLE 1/1 DOP GRIPPER & HOOKS - 70 LBS. MAX LOJ CL-GSY110 = ADJ. 20FT 1/16in SINGLE SUS RIPPER ON TOP 70 LBS. MAX LOAD (ORDE CL-GSY120 = ADJ. 20FT 1/16in SINGLE SUS RIPPER ON TOP 70 LBS. MAX LOAD (ORDE CACTORY-INSTALLED ON TOP	ISION KIT WITH Y- TIC TIE STRAPS - 16" 10FT. SUSPEN IAD (2 PER SET) 16" 20FT. SUSPEN IAD (2 PER SET) SPENSION CABLE ER 3 FOR 8FT.) SPENSION CABLE ER 3 FOR 8FT.)	CONNECTOR KEY HOLE S 70 LBS. MAX LOAD SION KIT WITH Y-CONNEC SION KIT WITH Y-CONNEC WITH Y HOOK ENDS. LOO	ET + 2 TOR & TOR & P	SCL-GS FACTORY	Y10 SCL-G		(Can be	e painted)
ank = No Option For Accessories PT-EM-CM1INT= INTERNAL EMERGENCY B PT-SEN-2MDR-36= PROGRAMMABLE MICR PT-HBC-125TL-BK = NEMA TWIST-LOCK PL PT-HBC-277TL-BK = NEMA TWIST-LOCK PL PT-HBC-125SB-BK = STRAIGHT BLADE PLI EC-3RC = OPTIONAL REMOTE	ROWAVE BI-LEVEL LUG 8FT, 15A, 125 LUG 8FT, 15A, 277	/		OPT-HBC-125SE	в-вк орт-нв	C-125TL-BK	орт-нвс-	-277TL-WH
Example: LSS-8FT-90W-MCTP-BK (FOR LS	SS 90W MCTP FIX	TURE 120-277V)		CONTRACT CONTRA				
	SS 90W MCTP FIX	TURE 120-277V)			MAINIT			
LSS-CB2 (ALIGN	SS 90W MCTP FIX IMENT BRACKET) NAL EMERGENCY	TURE 120-277V) BACKUP BATTERY)		OPT-EM-C	WITINT O	PT-SEN-2MDR-36		WEC-3RC