

JOB NAME: _____

DATE: _____

TYPE: _____

DIMENSIONS:

2.75" DIAMETER X 0.78" W



- PL120ADJ-30K-WH
- PL120ADJ-40K-WH
- PL120ADJ-50K-WH
- PL120ADJ-30K-BN
- PL120ADJ-40K-BN
- PL120ADJ-50K-BN
- PL120ADJ-30K-BK
- PL120ADJ-40K-BK
- PL120ADJ-50K-BK

120V LED ADJUSTABLE PUCK LIGHTS

Ideal for under cabinet, display cases or in low profile areas.

ELECTRICAL SPECIFICATIONS:

- Working Voltage: 120VAC
- Wattage: 4.5W
- Efficacy: 55LM/W

HOUSING SPECIFICATIONS:

- PC Housing
- Finish: White, Black & Brushed-Nickel
- 6 ft. cord with In-line switch
- Mounting: Recessed & Surface
- Screwless Trim

CERTIFICATIONS:



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP	FINISH
PL120ADJ-30K-WH	4.5W	120VAC	250LM	3000K	White
PL120ADJ-40K-WH	4.5W	120VAC	250LM	4000K	White
PL120ADJ-50K-WH	4.5W	120VAC	250LM	5000K	White
PL120ADJ-30K-BK	4.5W	120VAC	250LM	3000K	Black
PL120ADJ-40K-BK	4.5W	120VAC	250LM	4000K	Black
PL120ADJ-50K-BK	4.5W	120VAC	250LM	5000K	Black
PL120ADJ-30K-BN	4.5W	120VAC	250LM	3000K	Brushed-Nickel
PL120ADJ-40K-BN	4.5W	120VAC	250LM	4000K	Brushed-Nickel
PL120ADJ-50K-BN	4.5W	120VAC	250LM	5000K	Brushed-Nickel

LIGHTING SPECIFICATIONS:

- Total lumens: 250LM
- Dimmable: TRIAC Dimming
- color temperature: 3000K/4000K/5000K
- Beam Angle: 105°

WARRANTY: 3 years

